

### Product-Information

## Right-Angle Valve with ISO-K Flanges, DN 63-100 ISO-K

Manually Operated

Cat. No.: 10784



### Product-Description

These universal valves are ideal especially for smaller systems, where remote control is not essential. They may be also installed in larger systems, where backing pumps or condensate separators or similar units are to be cut off at longer intervals for maintenance purposes by maintenance personnel.

## **Product-Information**

### **Right-Angle Valve with ISO-K Flanges, DN 63-100 ISO-K**

Manually Operated

Cat. No.: 10784

#### Advantages to the User

- Gentle venting of systems
- Seal in both directions up to a pressure difference of 1.5 bar
- Easy manual operation, for an effortless vacuum-tight seal
- May also be used as a variable leak valve to roughly control gas flows
- Installation in any orientation and no restrictions as to the direction of flow

Stainless steel body, DN 100 ISO-K

**Product-Information**

**Right-Angle Valve with ISO-K Flanges, DN 63-100 ISO-K**

Manually Operated

Cat. No.: 10784

**Description**

**Unit**

**Value**

**Product-Information**

**Right-Angle Valve with ISO-K Flanges, DN 63-100 ISO-K**

Manually Operated

Cat. No.: 10784

Dimensions

Dimensions			
DN	ISO-K	63	100
A	mm	266	320
B	mm	124	164
C	mm	150	190
D	mm	88	108
E	mm	20	25

**Product-Information**

**Right-Angle Valve with ISO-K Flanges, DN 63-100 ISO-K**

Manually Operated

Cat. No.: 10784

Technical Drawing

